

BM3000

Static Compactor



Technical Specification



- > Safe & Easy to Operate
- > Reduces Vehicle Movements

Options

- > Smart Tec (status notifications)
- > SolarPac (solar power)
- > Photo Cell (auto start)
- > Extra Side Loading Door
- > Bin Lifter Trunion or Comb (BM3000 TL & BM3000 CL)
- > Oil Cooler
- > Enclosed Hopper

Models

- > BM3000 – Hand Loaded
- > BM3000 TL – Bin Lifter with Trunion
- > BM3000 CL – Bin Lifter with Comb

Dimensional Data

	BM3000	BM3000 TL&CL
Overall Width	2280mm	4335mm
Overall Length	3320mm	3320mm
Overall Height	2493mm	2465mm
Feed Height	1240mm	1240mm
Back Wall Clearance	500mm	500mm
Side Wall Clearance	1000mm	1000mm
Machine Weight	3500kg	4200kg
Charge Box Volume	2m ³	2m ³
Charge Box Width	1500mm	1500mm

Electrical Specifications

Supply Voltage	415VAC
Phase	3 Ph
Max Current	32 A
IP Rating	55
Control Circuit	24 vdc

Machine Specification

Compaction Ratio	4:1
Compaction Force	32 tonnes
Ram Penetration	300mm
Motor	7.5KW
System Pressure	145 bar
Cycle Time	45 secs
No. of Rams	2
75% & 100% Full Light	



415v, 32 amp 5 pin plug,
minimum C rated breaker.



DELIVERY &
CRANEAGE



TRAINING
PROVIDED



MADE IN THE
UNITED KINGDOM

