

BM32 WET

32yd³ Portable Waste Compactor



Technical Specification



- > Safe & Easy to Operate
- > Reduces Vehicle Movements
- > Liquid Retentive
- > Odour Free, tidy and efficient
- > Paddle Blade Design

Options

- > Smart Tec (Status Notifications)
- > SolarPac (Solar Power)
- > Various Hopper Configurations
- > Bin Lifter (BM32TL WET & BM32CL WET)
- > Full Safety Cage

Models

- > BM32 WET – Hand Loaded
- > BM32TL WET– Bin Lifter with Trunion
- > BM32CL WET– Bin Lifter with Comb

Electrical Specifications

Supply Voltage	415VAC
Phase	3 Ph
Max Current	32 A
IP Rating	55
Control Circuit	24 vdc



415v, 32 amp 5 pin plug,
minimum C rated breaker.



DELIVERY &
CRANEAGE



TRAINING
PROVIDED



MADE IN THE
UNITED KINGDOM

Dimensional Data

Overall Width	2360mm
Overall Length	6680mm
Overall Height	2629mm
Machine Weight	4900kg
Charge Box Depth	1534mm
Charge Box Width	1569mm
Charge Box Volume	2m ³
Load Aperture Dimensions	1589mm x 1569mm
Back Wall Clearance	500mm
Side Wall Clearance	1000mm

Machine Specification

Compaction Ratio	4:1
Compaction Force	32 tonnes
Ram Penetration	300mm
Motor	5.5KW
System Pressure	205 bar
Cycle Time	37 secs
No. of Rams	2
75% & 100% Full Light	