

BM800 H

Mill Specification Baler



Technical Specification



- > Suitable for Plastics, PET, Aluminium Cans, Cardboard and Film and Bulk Loading
- > Large Loading Aperture
- > Vertical Hydraulic Clamp Free Anti-Burst Door
- > Serrated Counter Shear Cutting Knives as Standard
- > Hi/Lo Baling Pressures
- > Auto Start – Photo Cell Controlled
- > Full Auto Bale Eject
- > Baling Wire Holder
- > Bale counter & Hours Run Display
- > IP 55 Rated for Outdoor Use
- > All safety requirements in accordance with CE directives.

Dimensional Data

Bale Weights	600kgs to 750kgs
Pressing Power	65 tonne
Cycle Time	75 seconds/ 47 second option
Overall Dimensions L x W x H	7715mm x 1650mm x 2990mm
Loading Aperture L x W	1750mm x 1050mm
Approximate Machine Weight	10000kgs
Maximum Bale Size W x H x L	1100mm x 1100mm x 1500mm
Wires Per Bale – Horizontal Tie	4/5
Motor	15kw
Control Voltage	24vDC
Power Supply	40 Amp, 400v 50hz (3~+N+E)

Options

- > Standard or Fast Cycle Time available
- > 18-22kw Power Pack Options
- > Side or End Conveyor Feed
- > Side Mounted Bin Lifter & Safety Cage
- > Oil Heater & Oil Cooler for challenging environments
- > Hook Lift Demountable option with A-Frame



400v, 40 amp, 5 pin plug, minimum C rated breaker

